

Digit Multimeter

H. TH1953/TH1963 Digit Multimeter

Features

- 4.3-inch LCD color display, Chinese and English menu
- 6 1/2 bit 1199999 digits reading (TH1963)
- 5 1/2 digit 119999 digits reading (TH1953)
- Test speed up to 1000 / s
- Small size, front and rear input terminal, easy to shelve
- Histogram, bar graph, trend chart display
- AC low frequency signal can be tested down to 3Hz
- Capacitance test function
- Up to 5V diode test voltage
- Stores data up to 10,000
- Fast Chinese and English help

Application

- Production line workbench
- Maintenance workbench
- Teaching laboratory
- Automated test equipment

Specifications

Model	TH1963		TH1953					
Display	4.3-inch LCD color display							
Display digits	1199999 digits reading		119999 digits reading					
Measurement parameters								
DC voltage, AC voltage, DC current, AC current, DC resistance, capacitance, frequency, breakdown, diode, temperature								
Display mode	Direct reading, histogram, bar graph, trend chart							
Measurement speed	Up to 1000 times / s							
Math function	Reset function, Min / Max / Average / Standard deviation, dB, dBm							
Common features	Range	Trigger mode	Reading-hold	Limit measurement				
	Auto / Manual	LOCAL: AUTO / SINGLE / EXT REMOTE: IMMEDIATE / BUS / EXT	Yes	HI, Lo and IN (PASS), with sound beep				
Technical Index	Uncertainty: \pm (% of reading +% of range), $T_{CAL}=25^{\circ}\text{C}$							
Parameters	Range / Test Range		Highest annual accuracy $T_{CAL} \pm 5^{\circ}\text{C}$	Highest temperature coefficient/ $^{\circ}\text{C}$				
			TH1963	TH1953				
DC voltage	100.0000 mV - 1000.000V		0.0035 + 0.0005	0.010 + 0.005				
True RMS AC voltage	100.000mV - 750.000V	3 - 5Hz	1.00 + 0.03	1.00 + 0.03				
		5 - 10Hz	0.35 + 0.03	0.38 + 0.03				
		10Hz - 20kHz	0.06 + 0.03	0.10 + 0.03				
		20 - 50kHz	0.12 + 0.05	0.15 + 0.05				
		50 - 100kHz	0.60 + 0.08	0.63 + 0.08				
		100 - 300kHz	4.00 + 0.50	4.00 + 0.50				
DC Resistance	10Ω-100MΩ, Test current: 10mA - 500nA		0.010 + 0.001	0.030 + 0.004				
DC current	100µA - 100mA		0.050 + 0.005	0.050 + 0.008				
	1A		0.100 + 0.010	0.100 + 0.010				
	3A		0.200 + 0.020	0.200 + 0.020				
	10A		0.120 + 0.010	0.200 + 0.010				
AC current	100µA - 1A	3kHz - 5kHz	0.10 + 0.04	0.20 + 0.04				
		5kHz - 10kHz	0.10 + 0.04	0.20 + 0.04				
		3Hz - 5kHz	0.23 + 0.04	0.25 + 0.04				
		5kHz - 10kHz	0.23 + 0.04	0.25 + 0.04				
		3Hz - 5kHz	0.15 + 0.04	0.3 + 0.04				
Frequency	100Hz - 1MHz	5kHz - 10kHz	0.15 + 0.04	0.3 + 0.04				
		3Hz - 10Hz	0.100	0.0002				
		10Hz - 100Hz	0.030	0.0002				
		100Hz - 1MHz	0.010	0.0002				
Diode	Square wave		0.010	0.0002				
	5V, Test current: 1mA		0.010 + 0.030	0.020 + 0.030				
	1kΩ, Test current: 1mA		0.010 + 0.030	0.030 + 0.030				
Capacitance	1.0000nF		1.0 + 0.5	0.02				
	10.000nF - 1.0000mF		0.5 + 0.1	0.02				
	10.000mF		1.0 + 0.5	0.02				
Temperature	PT100 (DIN/ IEC 751)		$\pm 0.05^{\circ}\text{C}$					
	5 kΩ Thermistor		$\pm 0.10^{\circ}\text{C}$					

**TH1963**

Standard RS232 USB HOST USB DEVICE LAN

option GPIB OR HANDLER

Rack mount (mm): 215(W) x 88(H) x 300(D)

Dimension (mm): 235(W) x 105(H) x 320(D)

Net weight: 2.7 kg

